

Pro Mod Rules Amendments 08-23-2023

Screw (C-rotor) Big Block Combo:

Big Block 4.9 bore space max

70% overdrive max ~~2375lbs~~ **2400lbs minimum (Added 25lbs)**

75% overdrive max allowed for 3 speed transmission ~~2400lbs~~ **2450lbs minimum (Added 50lbs)**

92% overdrive max 2600lbs minimum

110% overdrive max

2700lbs minimum

Add 25lbs for 4.9

bore space

~~Deduct 25lbs for 2-speed planetary or powerglide transmission-(Removed)~~

Deduct 75lbs for 4.84 bore space and smaller Non-481X/Hemi supercharged combinations.

(Add 25lbs lock-Up Transmissions also if you have a lock-up in the car no matter what you have to run the weight - no other power adder- Also If the over rule is *example applies to all C Combos* 70% then any combo 70.9 and below is acceptable) Manipulation of transmission or convertor pressure or volume, other than at the starting line, is prohibited on any non-lockup combination. Pressure manipulation control must be disarmed upon the release of the transbrake, or any other device used, when launching the vehicle for non-lockup combination.

Twin Turbo Big Block:

5.0" bore space 88mm max 2400lbs minimum

5.0" bore space 94mm max ~~2475lbs~~ **2500lbs minimum (Added 25lbs)**

5.0" bore space 98mm max ~~2550lbs~~ **2600lbs minimum (Added 50lbs)**

(Add 50lbs for 5.3 bore space)

(Add ~~25lbs~~ **50lbs lock-Up (added 25lbs)** Transmissions also if you have a lock-up in the car no matter what you have to run the weight - no other power adder) Manipulation of transmission or convertor pressure or volume, other than at the starting line, is prohibited on any non-lockup combination. Pressure manipulation control must be disarmed upon the release of the transbrake, or any other device used, when launching the vehicle for non-lockup combination)